P.O. Box 337 1880 E. Anvil Blvd. Hyrum, UT 84319

Office: 435.245.6081 Fax: 435.245.4476



Attic Card

R-Value	Settled Depth	Blown Depth	MIN WT/ SQFT	MAX SQ FT/ BAG	BAGS/ MSF 2X4/ 24
11	2.9	3.4	0.39	63.5	14.77
13	3.5	4.0	0.46	58.2	16.10
19	5.1	5.8	0.68	36.8	26.02
22	5.9	6.7	0.78	31.8	30.32
28	7.5	8.6	1.00	25.0	38.90
30	8.0	9.2	1.07	23.3	41.77
32	8.5	9.8	1.14	21.8	44.63
38	10.1	11.7	1.35	18.4	53.22
40	10.7	12.3	1.42	17.5	56.08
44	11.7	13.5	1.56	15.9	61.81
48	12.8	14.7	1.71	14.6	67.53
49	13.1	15.0	1.74	14.3	68.96
50	13.3	15.3	1.78	14.0	70.39
60	16.0	18.4	2.14	12.5	83.54

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 25 LBS. THESE ARE CALCULATED VALULES, THE ACTUAL NUMBERS MAY VARY. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1,000 SQ FT AND THE MAXIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VAULE HAS BEEN REACHED.

Address:	
Existing Insulation	Added Insulation
Type of Insulation:	<u>Cellulose</u>
Inches of Insulation:	
R-Value:	
TOTAL:	
(INCHES)	(R-VALUE)
Installing Company:	
Installer Signature:	
Date Installed:	

Customer Name: