P.O. Box 337 1880 E. Anvil Blvd. Hyrum, UT 84319



Office: 435.245.6081 Fax: 435.245.4476

Attic Card

R-Value	Settled Depth	Blown Depth	MIN WT/ SQFT	MAX SQ FT/ BAG	BAGS/ MSF 2X4/ 24
11	2.9	3.6	0.44	68.18	13.75
13	3.5	4.3	0.52	57.69	16.25
19	5.1	6.2	0.76	39.47	24.24
22	5.9	7.2	0.88	34.09	28.24
28	7.5	9.2	1.12	26.8	36.24
30	8.0	9.8	1.2	25	38.91
32	8.5	10.5	1.28	23.44	41.57
38	10.1	12.4	1.52	19.74	49.57
40	10.7	13.1	1.6	18.75	52.24
44	11.7	14.4	1.76	17.05	57.57
48	12.8	15.7	1.92	15.62	62.91
49	13.1	16	1.96	15.31	64.24
50	13.3	16.4	2	15.0	65.57
60	16.0	19.6	2.4	12.5	77.82

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS. THESE ARE CALCULATED VALUES, THE ACTUAL NUMBERS MAY VARY. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1,000 SQ FT AND THE MAXIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VAULE HAS BEEN REACHED.

Customer Name:_____ Address:_____

Existing Insulation Type of Insulation: Inches of Insulation: R-Value:_____

Added Insulation

Cellulose	

TOTAL:______(INCHES)

(R-VALUE)

Installing Company	:
Installer Signature:	
Date Installed:	